

Lighten up!

Our lightweight aerial FlexTube® fibre cables turn installation into an uplifting breeze.



Prysmian
Group

Linking
the Future



Our lightweight aerial FlexTube® fibre cables turn installation into an uplifting breeze.

Compared to Loose Tube solutions, aerial FlexTube® fibre cables are both smaller and lighter – while still accommodating up to 288 optical fibres. And in flexibility it has no equal, being immune to kinking. Add the easy access to the fibre and future-proofed performance, and you get a solution that's quicker to install and easier to maintain, reducing the cost of your network – today and tomorrow.



Unique technology

Our new technology offers higher performance and operational savings.



Multi diverse

Applicable to all relevant application areas.



Time saving

Easier to handle, particularly in connectivity items such as distribution and termination boxes.



Optical fibres

FlexTube® modules

Aramid reinforcement

GRP strength elements

HDPE outer sheath



Kink immune

The flexible design prevents the risk of attenuation increments or fibre breakage.



Future-proofed

Being extremely stable in temperature versus time, your network will be secured for decades.



Easy access

Finger access to the fibres means no specific tools are needed to open FlexTube.

PRYSMIAN GROUP

Offices Romania
Strada Milcov, Nr. 12A,
Slatina, 230077

Phone: +40 349 403 228
+40 349 403 210
+40 349 403 269

customercare.romania@prysmiangroup.com



prysmiangroup.ro

© All rights reserved by Prysmian Group 2022-05 | Version 1.

Technical data, dimensions and weights are subject to change. All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

Follow us

